

L.F. HIRE LTD

Product Information Sheet

8' Fixed U-Head Support (200mm)

DESCRIPTION

A heavy duty 8' (200mm) fixed u-head with spigot.

Designed to be used with acrow props or system scaffolding (kwikstage or cuplock), the main function of a u-head is to hold timber beams securely in place. Spigot measures 75mm long and is 16mm in diameter.

APPLICATIONS

- Designed to be used with acrow props or system scaffolding (Kwikstage or Cuplock).
- Holds timber beams securely in place during temporary support works.
- Suitable for use with trench struts and associated temporary works systems.

KEY DIMENSIONS

Info	Detail
Gap	220mm
Width	150mm
Height	100mm
Spigot Length	75mm
Spigot Diameter	16mm
Specification	BS1139 and EN74
Weight	4.25kg
Safe Working Load (SWL)	Dependent on supporting item (see notes below)

SAFE WORKING LOAD (SWL) GUIDANCE

Safe working load for a fixed U-head is dependent on the tube/item it is mounted within, as the downward force pushes directly through the fixed U-head into the mount. The fixed U-head itself does not bear any weight.

Always check the SWL of the supporting item you are using (acrow prop, tube, system scaffold etc.) before use. If in doubt, consult a competent person or structural engineer.

IMPORTANT NOTES

- Always ensure equipment is used on a firm, level base.
- Inspect equipment for damage before use.
- Do not exceed the SWL of the supporting system.
- Use appropriate PPE on site.