

Angle Drill LXT®

DDA351

18V • 13,5 Nm • 0 – 1 800 min⁻¹

Angle drill with keyless chuck for tight spaces

An angle drill with an 89 mm head for access to tight spaces. With a max. torque of 13.5 Nm. The tool's chuck capacity is 1.5 – 10 mm.



Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 1800 min ⁻¹
Max. Drilling Diameter in Wood	25 mm
Max. Drilling Diameter in Steel	10 mm
Driving Shank	24UNF / 3/8 "
Drill Chuck Capacity	1,5 - 10 mm
Angle length	88 mm
Max. Torque (2. Gear / 1. Gear)	- / 13,5 Nm
Drilling Capacity Wood (Self-feed bit)	50 mm
Vibration Level, Drilling into metal	≤ 2,5 m/s ²
Vibration Uncertainty (K Factor), Drilling into metal	1,5 m/s ²
Sound Pressure Level (L _{pA})	70 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)

User benefits

- The rubber coating on the handle ensures a firm working grip
- LED light illuminates the work site
- Reversing switch
- Variable speed control dial enables user to match the speed to the application for greater versatility
- Large paddle switch trigger for easy operation
- Electric brake for maximum productivity and increased operator safety
- Single sleeve keyless chuck enables easy bit installation/removal with one hand
- Battery protection system automatically shuts off power when the battery level is low

Link to product - www.makita.com



Related products

Optional AC

153489-2

Grip complete 125 mm



450128-8

Battery cover, LXT®, 14,4 – 18V



821550-0

Makpac case (2)



838040-6

Inner Tray for Makpac (2)



Other

[User manual](#)

[Parts drawing](#)