

# Auto Feed Screwdriver LXT®

## DFR750

18V • 45 – 75 mm • 4 000 min<sup>-1</sup>

### Quick screwdriving with auto-feed system

A cordless 18V LXT screwdriver for screw strips with a speed of 4 000 min<sup>-1</sup> and a robust aluminium auto-feed system for 45 – 75 mm screws. A precise depth control switch and screw guide ensure accuracy and prevent slanted screw feeds.



### ■ Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
Collated drywall screw	45 - 75 mm
No load speed	4000 min <sup>-1</sup>
Sound Pressure Level (L <sub>pA</sub> )	76 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Tool weight with battery	2,1 - 3,2 kg
Product Dimensions (L x W x H):	464 x 80 x 238 mm
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Driving Shank	1/4 "
Vibration Level, Screwdriving Without Impact	≤ 2,5 m/s <sup>2</sup>
Vibration Uncertainty (K Factor), Screwdriving Without Impact	1,5 m/s <sup>2</sup>

### ■ User benefits

- Depth adjustment
- Reversing switch
- Dust protected construction.
- Screw guide minimizes screw strip tangling
- Battery protection system automatically shuts off power when the battery level is low

Link to product - [www.makita.com](http://www.makita.com)



# Related products

## Optional AC

**141352-1**

Plastic Carrying Case



**194500-1**

Extension handle 890 – 990 mm



**450128-8**

Battery cover, LXT®, 14,4 – 18V



**P-67804**

Screw Bit, PH2, 177 mm, Ø 5 mm, 3



## Other

[User manual](#)

[Parts drawing](#)